

# Rittal – The System.



**E.B. Horsman & Son**  
*The Electrical Distributor of Choice!*

Faster – better – everywhere.



## Choose Better.

## Type 3R/4 for outdoor protection this summer.

### Best prices on the new Blue e, UL Type 3R/4 Top Therm wall-mounted cooling units!



Our Blue e Top Therm cooling units offer:

- Total cooling output of 0.50-2.50 kW
- NEMA 3R/4 for outdoor/indoor protection from harsh elements
- Up to 45% energy consumption savings
- Vandalism resistant controller
- Functionality & capacity tested


Promo ends  
August 31<sup>st</sup>



### Features



► Comfort Controller



► Nano Coated



► Eye Bolt (>1.000 W)



► Integrated condensate evaporator



► IoT Interface compatible

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

[www.rittal.ca](http://www.rittal.ca)



# Rittal – The System.

Faster – better – everywhere.

## Top Therm Blue e Wall-mounted air conditioners, UL Type 3R/4

Blue e UL Type 3R/4 Part No.	EER ** Energy Efficiency Ratio	Useful cooling output $Q_k$ BTU (W)	Dimensions H x W x D Inches (mm)	Voltage V, Hz
3303508	1.3/1.3	1570 (460)	24.5 x 11 x 13.8 (620 x 285 x 350)	230, 1~, 50 / 60
3303518	1.3	1877 (550)	24.5 x 11 x 13.8 (620 x 285 x 350)	115, 1~, 60
3304508	1.8/1.9	3753 (1100)	40.2 x 15.9 x 16.1 (1020 x 405 x 410)	230, 1~, 50 / 60
3304518	1.7/1.5	3753 (1100)	40.2 x 15.9 x 16.1 (1020 x 405 x 410)	115, 1~, 50 / 60
3304548	1.5/1.7	3924 (1150)	40.2 x 15.9 x 16.1 (1020 x 405 x 410)	400, 3~, 50 460, 3~, 60
3305508	2.4/2.4	5238 (1540)	40.2 x 15.9 x 16.1 (1020 x 405 x 410)	230, 1~, 50 / 60
3305518	2.2/2.2	5238 (1540)	40.2 x 15.9 x 16.1 (1020 x 405 x 410)	115, 1~, 60
3305548	2.3/2.1	5084 (1490)	40.2 x 15.9 x 16.1 (1020 x 405 x 410)	400, 3~, 50 400, 3~, 60
3329508	2.1/2.1	8564 (2510)	64.9 x 15.9 x 17.3 (1650 x 405 x 440)	230, 1~, 50 / 60
3329518	1.9/1.9	8564 (2510)	64.9 x 15.9 x 17.3 (1650 x 405 x 440)	115, 1~, 60
3329548	1.8/1.5	8292 (2430)	64.9 x 15.9 x 17.3 (1650 x 405 x 440)	400, 3~, 50 400, 3~, 60

Our full range of climate control solutions is on the internet. Note: For connection diagrams, see latest assembly instructions under [www.rittal.ca/climatecontrol](http://www.rittal.ca/climatecontrol).

\*\*EER (Energy Efficiency Ratio = Watts of cooling capacity divided by watts of power consumption).

Available at E.B. Horsman & Son

Phone: 1-888-467-7626

Email: [info@horsman.com](mailto:info@horsman.com) • Online: [www.ebhorsman.com](http://www.ebhorsman.com)



ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES